

Product Details

Product Range	Kite Breeze
Texture Finish	Milled
Colours	Paperbark Beige, Desert Red, Sunset Sand & Dawn Grey
Product Code	
Format	
Place of Manufacture	Jandakot, Western Australia
Length (mm)	300
Width (mm)	90
Height (mm)	300
Size	300x90x300
Core Volume (%)	-
Characteristic Unconfined Compressive Strength (f 'uc) MPa	-
Minimum Shell Thickness (mm)	-
Weight	8.49
Units Per Tonne	117.79
Units Per Pallet	96
Units per Square Metre	11.11
Durability Class	General Purpose
Slip Resistance	
Wall Mass Inc Hollow	-
Solar Absorption Rating	-
LRV	-
FRL	-
EPD	Yes
Declare	No
Recycled Content %	-

Diagram



Fire Resistance Levels^

Structural Adequacy	-
Integrity	-
Insulation	-

Notes

Tested as per AS/NZS 4456: 2003 and 4586: 2013. This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact GB Masonry for confirmation of product specification

This data represents average results from production lots based on the results achieved by samples selected at random for testing. Figures are accurate at date of publication and subject to change without notice. Contact us for confirmation of product specification. Tested as per AS/NZS 4455.1: 2008 and 4456: 2003. Fire resistance levels as per AS3700: 2018. Acoustic opinion derived from Day Design Pty Ltd. 2012. Tested in accordance with AS 1191:1001 and AS/NZS 1276.1:1999. ^When reinforced and Srf 36: 240 minutes. Please note FRL applies up to 3m high - restrained on top